



Inspiring green-energy since 2003

## PERC Technology

# AE PLUS MONOCRYSTALLINE PV MODULES AE M6-72 Series 365 W-385W

<b>72</b> CELLS	<b>MICRO-CRACK FREE</b>	<b>PID RESISTANT</b>	<b>SALT CORROSION RESISTANT</b>	<b>SAND RESISTANT</b>	<b>AMMONIA RESISTANT</b>	<b>HIGHLY STABLE AND TOUGH</b>
--------------------	-------------------------	----------------------	---------------------------------	-----------------------	--------------------------	--------------------------------


**✓ GERMAN QUALITY**  
AE Solar photovoltaic modules are produced using high quality materials, automated robotic lines, German technology and standards.

**+ PLUS-SORTING**  
Higher yield due to plus-sorting from 0 up to +5 Wp guarantees the high system efficiency and yield stability.

**🕒 PERFORMANCE GUARANTEE**  
AE Solar assures high investment, security and warranty claims by providing linear performance guarantee of 30 years and 12 years of product warranty.

**📄 CERTIFICATES**  
Lining with international standards, AE Solar Photovoltaic modules are tested and certified under extreme stress conditions and it can bear harsh environment influences.

### OUR PERFORMANCE GUARANTEE



**30**  
years  
Performance Guarantee

**12**  
years  
Product Warranty



Deutsche  
Qualität  
Garantiert

# TECHNICAL DATA

## AE M6-72 Series 365W-385W

### SPECIFICATIONS

		AE365M6-72	AE370M6-72	AE375M6-72	AE380M6-72	AE385M6-72
Nominal Max. Power	Pmax (Wp)	365	370	375	380	385
Maximum power voltage	Vmp(V)	39.58	39.63	39.66	39.71	39.73
Maximum power current	Imp (A)	9.22	9.34	9.46	9.57	9.69
Open-circuit voltage	Voc(V)	47.42	47.48	47.53	47.59	47.81
Short-circuit current	Isc (A)	9.65	9.69	9.75	9.82	9.95
Module efficiency	(%)	18.81	19.07	19.33	19.58	19.84
Power tolerance	Pmax (Wp)	0 / + 5				
Maximum system voltage DC	(V)	1000				
Operating temperature	(°C)	-40 to +85				
Temp. coefficients of Pmax	(%/°C)	-0.38				
Temp. coefficients of Voc	(%/°C)	-0.29				
Temp. coefficients of Isc	(%/°C)	0.05				
Nom. Operating cell temp.(NOCT)	(°C)	45±2				

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m<sup>2</sup> with spectrum AM 1.5 and a cell temperature of 25°C.


### MATERIAL CHARACTERISTICS

Cell type	Mono-crystalline 156.75mm × 156.75mm
No. of cells	72 (6 × 12)
Dimensions	1956 × 992 × 40mm
Weight	21 kg
Junction box	IP 67 MC 4 compatible
Output cable	1 × 4.0mm <sup>2</sup> , 1200mm length or customised
Connector type	MC 4 compatible
Hail resistance	Max. Ø 28 mm, at 23 m/s
Wind load	2400 Pa / 244 kg/m <sup>2</sup>
Mechanical load	5400 Pa / 550 kg/m <sup>2</sup>


### PACKAGING INFORMATION

Packing configuration	56pcs/double pallet	52pcs/double pallet
Loading Capacity	672 pcs / 40HQ	624 pcs / 40GP
Size / pallet (mm)	1990x1120x2410	1990x1120x2250
Weight	1300 kg / pallet	1192 kg / pallet

### CERTIFICATES



### DIMENSIONS



AES-DSH2019 V.002

All rights reserved. Specifications included in this data sheet are subject to change without notice.

**AE Solar GmbH**

Messerschmittring 54  
86343 Königsbrunn  
Germany

Tel.: +49 8231 92 92 52 2

Fax: +49 8231 97 82 68 9

Email: sales@ae-solar.com

Web: www.ae-solar.com